# NSN 5930-01-268-6484

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-268-6484

#### **Hazardous Locations/environmental Protection:**

Shock resistant and watertight

**Overall Length:** 

3.520 inches

**Overall Height:** 

1.740 inches

**Overall Width:** 

2.120 inches

#### **Unthreaded Mounting Hole Diameter:**

0.189 inches single mounting facility

#### **Individual Section Quantity:**

1

#### **Longest Horizontal Distance Between Mounting Centers:**

1.620 inches single mounting facility

#### **Longest Vertical Distance Between Mounting Centers:**

1.250 inches single mounting facility

# **Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

## **Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

# **Features Provided:**

Legend plate

#### **Contact Voltage Rating In Volts:**

440.0 highest ac voltage rating at sea level

# **Switch Actuator Momentary Position:**

Counterclockwise single actuator

## **Mounting Facility Pattern:**

Four position rectangular single mounting facility

#### **Switch Actuator Indexing Position Quantity:**

3 single actuator

# **Terminal Type:**

Tab w/screw

#### **Contact Switching Action:**

Breaks before makes single section periphery

## **Switch Actuator Positioning Increment:**

90.0 degrees single actuator

# **Switch Actuator Stop Device Type:**

Fixed-adjustable stops single actuator

# **Contact Load Current Rating:**

750.0 milliamperes inductive load highest ac voltage rating at sea level

#### **Special Features:**

Legend plate reads off/test/auto

# NSN 5930-01-268-6484

Rotary Switch - Page 2 of 2



Style	Design	ator:

Tap, circuit selector

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0