NSN 5930-01-269-5067

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-269-5067

| Body Style: |
|--|
| Panel mount |
| Hazardous Locations/environmental Protection: |
| Moisture resistant and shock proof |
| Overall Length: |
| 0.755 inches |
| Overall Height: |
| 3.060 inches |
| Overall Width: |
| 0.755 inches |
| Body Length: |
| 0.755 inches |
| Body Width: |
| 0.755 inches |
| Body Height: |
| 2.250 inches |
| Case Material: |
| Metal |
| Actuator Length: |
| 0.755 inches |
| Actuator Style: |
| Rectangular |
| Actuator Width: |
| 0.755 inches |
| Actuator Color: |
| Red single actuator and yellow single actuator |
| Illuminated Actuator Color: |
| Red single actuator and yellow single actuator |
| Actuator Inscription: |
| Alarm ack/temp alarm single actuator |
| Illuminated Actuator Color Sequence: |
| Upper half of actuator yellow lower half of actuator red |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Features Provided: |
| Holding solenoid |
| Nonpile-up Contact Arrangement: |

4 pole, double throw, one position momentary single switch unit

NSN 5930-01-269-5067

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 5.000 amperes resistive ac

Special Features:

Horizontal split lens

Precious Material And Location:

Contact surfaces gold and contacts silver

Unable To Decode:

Unable to decode and unable to decode

Terminal Type And Quantity:

19 pin

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A053a0