NSN 5930-01-269-5074

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-269-5074

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Moisture resistant and shock proof

Overall Length:

0.755 inches

Overall Height:

3.060 inches

Overall Width:

0.755 inches

Body Length:

0.755 inches

Body Width:

0.755 inches

Body Height:

2.250 inches

Case Material:

Metal

Actuator Length:

0.755 inches

Actuator Style:

Rectangular

Actuator Width:

0.755 inches

Actuator Color:

Red single actuator and yellow single actuator

Illuminated Actuator Color:

Red single actuator and yellow single actuator

Actuator Inscription:

Tube 6 alm ack/alarm single actuator

Illuminated Actuator Color Sequence:

Upper half of actuator yellow lower half of actuator red

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Holding solenoid

Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

NSN 5930-01-269-5074

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 5.000 amperes resistive ac

Special Features:

Horizontal split lens

Precious Material And Location:

Contact surfaces gold and contacts silver

Unable To Decode:

Unable to decode and unable to decode

Terminal Type And Quantity:

19 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0