## NSN 5930-01-269-8132

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-269-8132

| Body Style:  |
|--|
| Panel mount  |
| Hazardous Locations/environmental Protection:  |
| Moisture resistant and shock proof   |
| Overall Length:  |
| 0.755 inches   |
| Overall Height:  |
| 3.060 inches   |
| Overall Width:   |
| 0.755 inches   |
| Body Length:   |
| 0.755 inches   |
| Body Width:  |
| 0.755 inches   |
| Body Height:   |
| 2.250 inches   |
| Case Material:   |
| Metal  |
| Actuator Length:   |
| 0.755 inches   |
| Actuator Style:  |
| Rectangular  |
| Actuator Width:  |
| 0.755 inches   |
| Actuator Color:  |
| Red single actuator and yellow single actuator   |
| Illuminated Actuator Color:  |
| Red single actuator and yellow single actuator   |
| Actuator Inscription:  |
| Tube 3 alm ack/alarm single actuator   |
| Illuminated Actuator Color Sequence:   |
| Upper half of actuator yellow lower half of actuator red   |
| Maximum Voltage Rating In Volts:   |
| 115.0 ac and 28.0 dc   |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |
| Panel  |
| Features Provided:   |
| Holding solenoid   |
| Nonpile-up Contact Arrangement:  |
| A male place to the service of the s |

4 pole, double throw, one position momentary single switch unit

## NSN 5930-01-269-8132

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 5.000 amperes resistive ac

**Special Features:** 

Horizontal split lens

**Precious Material And Location:** 

Contact surfaces gold and contacts silver

**Unable To Decode:** 

Unable to decode and unable to decode

**Terminal Type And Quantity:** 

19 pin

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A053a0