NSN 5930-01-269-8141

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-269-8141

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Moisture resistant and shock proof
Overall Length:
0.755 inches
Overall Height:
3.060 inches
Overall Width:
0.755 inches
Body Length:
0.755 inches
Body Width:
0.755 inches
Body Height:
2.250 inches
Case Material:
Metal
Actuator Length:
0.755 inches
Actuator Style:
Rectangular
Actuator Width:
0.755 inches
Actuator Color:
Red single actuator and yellow single actuator
Illuminated Actuator Color:
Red single actuator and yellow single actuator
Actuator Inscription:
Tube 15 alm ack/alarm single actuator
Illuminated Actuator Color Sequence:
Upper half of actuator yellow lower half of actuator red
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Holding solenoid
Nonpile-up Contact Arrangement:
A note that there is no extra an arrangement of the control of

4 pole, double throw, one position momentary single switch unit

NSN 5930-01-269-8141

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 5.000 amperes resistive ac

Special Features:

Horizontal split lens

Precious Material And Location:

Contact surfaces gold and contacts silver

Unable To Decode:

Unable to decode and unable to decode

Terminal Type And Quantity:

19 pin

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A053a0