NSN 5930-01-270-0583

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-270-0583

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Driptight and dustproof and moisture resistant
Overall Length:
2.355 inches
Overall Height:
0.960 inches
Overall Width:
0.960 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.275 inches
Actuator Width:
0.620 inches
Actuator Color:
Black single actuator and black single actuator
Illuminated Actuator Color:
White single actuator
Actuator Inscription:
E-call rel single actuator
Maximum Voltage Rating In Volts:
28.0 dc and 115.0 ac
Mounting Surface To Terminal End Distance:
Between 1.720 inches and 1.880 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Actuator seal and full display lens
Nonpile-up Contact Arrangement:
4 pole double throw one position momentary single switch unit

NSN 5930-01-270-0583

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

6 tab, solder lug and 12 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0