

View Online at <https://aerobasegroup.com/nsn/5930-01-270-0662>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Moisture proof

Overall Length:

1.680 inches

Overall Height:

0.875 inches

Overall Width:

0.875 inches

Bushing Length:

0.312 inches

Body Length:

0.771 inches

Case Material:

Metal

Actuator Diameter:

0.375 inches

Actuator Height:

0.250 inches

Actuator Color:

Red single actuator

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

5811-01-180-8880 pulse train separator td-1208a/msq-103

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.000 amperes inductive dc and 1.500 amperes lamp dc

Special Features:

Neoprene washer

Thread Series Designator:

Unef

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0