NSN 5930-01-270-0662

Push Switch - Page 1 of 2

Thread Class:

Neoprene washer



View Online at https://aerobasegroup.com/nsn/5930-01-270-0662

2a
Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Moisture proof
Overall Length:
1.680 inches
Overall Height:
0.875 inches
Overall Width:
0.875 inches
Bushing Length:
0.312 inches
Body Length:
0.771 inches
Case Material:
Metal
Actuator Diameter:
0.375 inches
Actuator Height:
0.250 inches
Actuator Color:
Red single actuator
Maximum Voltage Rating In Volts:
28.0 dc
End Application:
5811-01-180-8880 pulse train separator td-1208a/msq-103
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thready Qty Per Inch (tpi):
24
Thread Size:
0.625 inches
Nonpile-up Contact Arrangement:
2 two circuit, double break/double make, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
$4.000 \ \text{amperes}$ resistive dc and $2.000 \ \text{amperes}$ inductive dc and $1.500 \ \text{amperes}$ lamp dc
Special Features:

NSN 5930-01-270-0662

Push Switch - Page 2 of 2



Thread Series Designator:
Unef
Terminal Type And Quantity:
8 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0