NSN 5930-01-270-1823

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-270-1823

Hazardous Locations/environmental Protection:
Corrosion proof and explosion proof
Overall Length:
1.770 inches
Body Diameter:
0.250 inches
Body Length:
0.870 inches
Overall Diameter:
0.250 inches
Tempurature Sensing Element Type:
Internal sensor
Mounting Method:
Terminal
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Wire lead
Contact Load Current Rating:
0.5 amperes resistive load second voltage
olo amporco reciciivo icaa cocona voltago
Contact Adjustability:
Contact Adjustability:
Contact Adjustability: Actuation point not adjustable
Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating:
Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating: 50.00 actuation point degrees celsius
Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating: 50.00 actuation point degrees celsius Contact Voltage Rating In Volts:
Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating: 50.00 actuation point degrees celsius Contact Voltage Rating In Volts: 120.0 ac at sea level first voltage
Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating: 50.00 actuation point degrees celsius Contact Voltage Rating In Volts: 120.0 ac at sea level first voltage Special Features:
Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating: 50.00 actuation point degrees celsius Contact Voltage Rating In Volts: 120.0 ac at sea level first voltage Special Features: Electro-ceramic sensor
Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating: 50.00 actuation point degrees celsius Contact Voltage Rating In Volts: 120.0 ac at sea level first voltage Special Features: Electro-ceramic sensor Media For Which Designed:
Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating: 50.00 actuation point degrees celsius Contact Voltage Rating In Volts: 120.0 ac at sea level first voltage Special Features: Electro-ceramic sensor Media For Which Designed: Gas or liquid
Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating: 50.00 actuation point degrees celsius Contact Voltage Rating In Volts: 120.0 ac at sea level first voltage Special Features: Electro-ceramic sensor Media For Which Designed: Gas or liquid Style Designator:
Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating: 50.00 actuation point degrees celsius Contact Voltage Rating In Volts: 120.0 ac at sea level first voltage Special Features: Electro-ceramic sensor Media For Which Designed: Gas or liquid Style Designator: Cylindrical
Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating: 50.00 actuation point degrees celsius Contact Voltage Rating In Volts: 120.0 ac at sea level first voltage Special Features: Electro-ceramic sensor Media For Which Designed: Gas or liquid Style Designator: Cylindrical Shelf Life:

No

Demilitarization:

NSN 5930-01-270-1823

Thermostatic Switch - Page 2 of 2



Fiig:

A048b0