## NSN 5930-01-270-2075

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-270-2075

| Body Style:   |
|---|
| Panel mount   |
| Hazardous Locations/environmental Protection:                 |
| Moisture resistant and shock proof                            |
| Overall Length:   |
| 0.755 inches  |
| Overall Height:   |
| 3.060 inches  |
| Overall Width:  |
| 0.755 inches  |
| Body Length:  |
| 0.755 inches  |
| Body Width:   |
| 0.755 inches  |
| Body Height:  |
| 2.250 inches  |
| Case Material:  |
| Metal   |
| Actuator Length:  |
| 0.755 inches  |
| Actuator Style:   |
| Rectangular   |
| Actuator Width:   |
| 0.755 inches  |
| Actuator Color:   |
| Red single actuator and yellow single actuator                |
| Illuminated Actuator Color:                                   |
| Red single actuator and yellow single actuator                |
| Actuator Inscription:   |
| Tube 24 alm ack/alarm single actuator                         |
| Illuminated Actuator Color Sequence:                          |
| Upper half of actuator yellow lower half of actuator red      |
| Maximum Voltage Rating In Volts:                              |
| 115.0 ac and 28.0 dc  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Method:  |
| Panel   |
| Features Provided:  |
| Holding solenoid  |
| Nonpile-up Contact Arrangement:                               |
| 4 note double throw one position momentary single switch unit |

## NSN 5930-01-270-2075

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 5.000 amperes resistive ac

**Special Features:** 

Horizontal split lens

**Precious Material And Location:** 

Contact surfaces gold and contacts silver

**Unable To Decode:** 

Unable to decode and unable to decode

**Terminal Type And Quantity:** 

19 pin

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A053a0