NSN 5930-01-270-4584

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-270-4584

Body Style:						
Hole mounted						
Center To Center Distance Between Mounting Facilities Parallel To Length:						
0.375 inches						
Body Length:						
0.781 inches						
Body Width:						
0.250 inches						
Body Height:						
0.484 inches						
Unthreaded Mounting Hole Diameter:						
0.088 inches						
Actuator Length:						
0.578 inches						
Actuator Style:						
Roller arm						
Actuator Free Position Height:						
0.725 inches						
Actuator Roller Diameter:						
0.188 inches						
Actuator Roller Width:						
0.125 inches						
Maximum Voltage Rating In Volts:						
125.0 ac and 30.0 dc						
Inclosure Type:						
Fully enclosed						
Mounting Method:						
Unthreaded hole						
Nonpile-up Contact Arrangement:						
1 pole, single throw, normally closed, momentary action single switch unit						
Switch Actuating Force:						
26.0 grams						
Actuator Movement:						
Between 0.141 pretravel inches and 0.030 overtravel inches and 0.020 differential inches						
Contact Load Current Rating At Maximum Rated Voltage:						
0.100 amperes resistive dc and 0.100 amperes resistive ac						
Precious Material And Location:						
Contacts gold						
Terminal Type And Quantity:						
2 tab, solder lug						
Shelf Life:						

N/a

NSN 5930-01-270-4584

Sensitive Switch - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A053a0