

View Online at <https://aerobasegroup.com/nsn/5930-01-270-6138>

Hazardous Locations/environmental Protection:

Oiltight and dusttight

Overall Length:

3.372 inches

Overall Height:

6.004 inches

Overall Width:

2.370 inches

Body Height:

3.000 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Longest Horizontal Distance Between Mounting Centers:

2.720 inches

Longest Vertical Distance Between Mounting Centers:

2.720 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port and tamper proof cap

Contact Action Stimulus:

Increase

Proof Pressure:

7000.00 pounds per square inch gage

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

50.0 milliamperes resistive load third voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+130.00/+1500.00 actuation point pounds per square inch gage and +100.00/+1400.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

Internal actuation point screw

Contact Voltage Rating In Volts:

600.0 ac at sea level second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0