

View Online at <https://aerobasegroup.com/nsn/5930-01-270-6138>

**Hazardous Locations/environmental Protection:**

Oiltight and dusttight

**Overall Length:**

3.372 inches

**Overall Height:**

6.004 inches

**Overall Width:**

2.370 inches

**Body Height:**

3.000 inches

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.720 inches

**Longest Vertical Distance Between Mounting Centers:**

2.720 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Electrical access port and tamper proof cap

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

7000.00 pounds per square inch gage

**Mounting Facility Pattern:**

Two position diagonal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

50.0 milliamperes resistive load third voltage

**Contact Adjustability:**

Actuation point adjustable

**Contact Adjustment Range:**

+130.00/+1500.00 actuation point pounds per square inch gage and +100.00/+1400.00 deactuation point pounds per square inch gage

**Contact Adjustment Type:**

Internal actuation point screw

**Contact Voltage Rating In Volts:**

600.0 ac at sea level second voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0