

View Online at <https://aerobasegroup.com/nsn/5930-01-270-7856>

**Thread Class:**

2b 1st mounting facility

**Individual Section Quantity:**

12

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Facility Circle Radius:**

1.610 inches 1st mounting facility

**Mounting Method:**

Threaded hole 1st mounting facility and bracket 1st mounting facility

**Features Provided:**

Actuator knob

**Thread Size:**

0.250 inches 1st mounting facility

**Contact Voltage Rating In Volts:**

500.0 ac at sea level

**Mounting Facility Pattern:**

Four position circular 1st mounting facility

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Criticality Code Justification:**

Feat

**Terminal Type:**

Connector, receptacle

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Contact Load Current Rating:**

30.0 amperes resistive load dc at sea level

**Special Features:**

Item must comply with requirements of desc production standard no. L03917; for navy nuclear propulsion plant products only; mtg bracket located left side

**Thread Series Designator:**

Unc 1st mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0