

View Online at <https://aerobasegroup.com/nsn/5930-01-271-1738>

Thread Class:

2a single threaded bushing

Hazardous Locations/environmental Protection:

Vibration resistant and moisture resistant and salt spray resistant

Overall Length:

0.373 inches

Body Length:

0.170 inches

Temperature Sensing Element Type:

Internal sensor

Width Across Flats:

0.281 inches

Operating Temperature Rating:

Between -80.0 degrees fahrenheit and 400.0 degrees fahrenheit

Mounting Method:

Threaded bushing

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single threaded bushing

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

1.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

245.00 actuation point degrees fahrenheit and 215.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

30.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Style Designator:

Plug

Thread Series Designator:

Unf single threaded bushing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0