## NSN 5930-01-271-5385

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-271-5385

**Thread Class:** 2a single mounting facility Thread Length:

0.250 inches single mounting facility

**Overall Length:** 

1.242 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.094 inches single actuator

**Shaft Diameter:** 

0.125 inches single actuator

**Shaft Length:** 

0.375 inches single actuator

**Overall Diameter:** 

0.500 inches

**Individual Section Quantity:** 

**Nonturn Device Type:** 

Flatted bushing at 3: 00 o'clock

**End Application:** 

A-10

1

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

1 single section rear

**Throw Quantity:** 

8 single section rear

**Mounting Method:** 

Threaded bushing w/panel seal single mounting facility

**Thread Size:** 

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

8 single actuator

**Shaft Type:** 

Round, flatted single actuator

**Criticality Code Justification:** 

Feat

**Terminal Type:** 

Tab, solder lug

## NSN 5930-01-271-5385

Rotary Switch - Page 2 of 2

A052b0



Contact Switching Action:
Breaks before makes single section rear
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
200.0 milliamperes resistive load dc at sea level
Special Features:
Weapon system essential
Precious Material And Location:
Common ring surfaces and rotor contact and terminals silver and common ring and rotor contact and terminal surfaces gold
Precious Material:
Gold and silver
Style Designator:
Snap or line
Thread Series Designator:
Unf single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: