NSN 5930-01-272-0425

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Body Style:Panel mount

Watertight

Overall Length: 0.950 inches Overall Height: 2.907 inches Overall Width: 0.800 inches



View Online at https://aerobasegroup.com/nsn/5930-01-272-0425

Body Length:
0.688 inches
Body Width:
0.688 inches
Case Material:
Metal
Actuator Length:
0.750 inches
Actuator Style:
Rectangular
Actuator Height:
0.482 inches
Actuator Width:
0.750 inches
Actuator Color:
Black single actuator
Actuator Inscription:
On/off single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
Approach light system (als)
Inclosure Type:
Fully enclosed
Features Provided:
Holding solenoid
Nonpile-up Contact Arrangement:
2 pole, double throw, three positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
1.000 amperes resistive dc and 7.000 amperes resistive ac
Special Features:
4a3s6, 7, ti 6850.56, fa 9993, dual mode high intensity approach lighting system (alsf-2/ssalr), sec 1-10, pg 8-65

NSN 5930-01-272-0425

Push Switch - Page 2 of 2



Precious	Material	And I	Location:

Contacts silver

Terminal Type And Quantity:

6 turret and 3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0