

View Online at <https://aerobasegroup.com/nsn/5930-01-272-0425>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

0.950 inches

**Overall Height:**

2.907 inches

**Overall Width:**

0.800 inches

**Body Length:**

0.688 inches

**Body Width:**

0.688 inches

**Case Material:**

Metal

**Actuator Length:**

0.750 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.482 inches

**Actuator Width:**

0.750 inches

**Actuator Color:**

Black single actuator

**Actuator Inscription:**

On/off single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

Approach light system (als)

**Inclosure Type:**

Fully enclosed

**Features Provided:**

Holding solenoid

**Nonpile-up Contact Arrangement:**

2 pole, double throw, three positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 7.000 amperes resistive ac

**Special Features:**

4a3s6, 7, ti 6850.56, fa 9993, dual mode high intensity approach lighting system (alsf-2/ssalr), sec 1-10, pg 8-65

**Precious Material And Location:**

Contacts silver

**Terminal Type And Quantity:**

6 turret and 3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A053a0