NSN 5930-01-272-2296

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-272-2296 **Body Style: Bushing mounted Actuator Style:** Round **Actuator Diameter:** 0.250 inches **Actuator Height:** 0.250 inches **Actuator Free Position Height:** 0.875 inches **Housing Length:** 1.400 inches **Housing Bushing Length:** 0.625 inches **Maximum Voltage Rating In Volts:** 28.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing **Thread Size:** 0.469 inches **Nonpile-up Contact Arrangement:** 4 pole, double throw, one position momentary single switch unit **Switch Release Force:** 64.0 ounces **Switch Actuating Force:** Between 96.0 ounces and 192.0 ounces **Actuator Movement:** Between 0.040 pretravel inches and 0.210 overtravel inches and 0.020 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 7.000 amperes resistive dc and 2.500 amperes inductive dc and 4.000 amperes motor dc **Thread Series Designator:** Unef **Terminal Type And Quantity:** 1 connector, receptacle Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5930-01-272-2296

Sensitive Switch - Page 2 of 2



Fiig:

A053a0