

View Online at <https://aerobasegroup.com/nsn/5930-01-272-2296>

**Body Style:**

Bushing mounted

**Actuator Style:**

Round

**Actuator Diameter:**

0.250 inches

**Actuator Height:**

0.250 inches

**Actuator Free Position Height:**

0.875 inches

**Housing Length:**

1.400 inches

**Housing Bushing Length:**

0.625 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

4 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

64.0 ounces

**Switch Actuating Force:**

Between 96.0 ounces and 192.0 ounces

**Actuator Movement:**

Between 0.040 pretravel inches and 0.210 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 2.500 amperes inductive dc and 4.000 amperes motor dc

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

1 connector, receptacle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0