NSN 5930-01-272-4126

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-272-4126

View Online at https://aerobasegroup.com/nsn/5930-01-272-4126
Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
3.380 inches
Overall Height:
1.000 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
2.950 inches
Case Material:
Metal
Actuator Length:
1.000 inches
Actuator Style:
Rectangular
Actuator Height:
0.430 inches
Actuator Width:
0.750 inches
Illuminated Actuator Color:
Yellow single actuator and red single actuator
Actuator Inscription:
Range 16 miles single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
2.950 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Rfi shielding and full display lens
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

NSN 5930-01-272-4126

Push Switch - Page 2 of 2



Precious Material And Location:
Contact silver
Terminal Type And Quantity:
1 socket, integrated wire termination
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0