## NSN 5930-01-272-4130

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-272-4130

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
3.380 inches
Overall Height:
1.000 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
1.000 inches
Case Material:
Metal
Actuator Length:
1.000 inches
Actuator Style:
Rectangular
Actuator Height:
0.430 inches
Actuator Width:
0.750 inches
Illuminated Actuator Color:
Yellow single actuator and red single actuator
Actuator Inscription:
Pads mode single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
2.950 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Rfi shielding and full display lens
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

## NSN 5930-01-272-4130

Push Switch - Page 2 of 2



Precious Material And Location:
Contact silver
Terminal Type And Quantity:
1 socket, integrated wire termination
Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A053a0