## NSN 5930-01-272-4133

Push Switch - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5930-01-272-4133	
Body Style:	
Panel mounted	
Hazardous Locations/environmental Protection:	
Explosion proof and humidity resistant	
Overall Length:	
3.380 inches	
Overall Height:	
1.000 inches	
Overall Width:	
0.750 inches	
Body Width:	
0.750 inches	
Body Height:	
1.000 inches	
Case Material:	
Metal	
Actuator Length:	
1.000 inches	
Actuator Style:	
Rectangular	
Actuator Height:	
0.430 inches	
Actuator Width:	
0.750 inches	
Illuminated Actuator Color:	
Yellow single actuator and red single actuator	
Actuator Inscription:	
Target symbols single actuator	
Maximum Voltage Rating In Volts:	
115.0 ac and 28.0 dc	
Mounting Surface To Terminal End Distance:	
2.950 inches	
Inclosure Type:	
Fully enclosed	
Mounting Method:	
Panel	
Features Provided:	
Rfi shielding and full display lens	
Nonpile-up Contact Arrangement:	
2 pole, double throw, one position momentary single switch unit	
Contact Load Current Rating At Maximum Rated Voltage:	

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

## NSN 5930-01-272-4133

Push Switch - Page 2 of 2



Precious Material And Location:
Contact silver
Terminal Type And Quantity:
1 socket, integrated wire termination
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A053a0