NSN 5930-01-272-4146

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Humidity resistant and explosion proof

Between 1.240 inches and 1.260 inches

Body Style: Panel mount

Overall Length:

Overall Height: 3.430 inches



View Online at https://aerobasegroup.com/nsn/5930-01-272-4146

Overall Width:
Between 0.990 inches and 1.010 inches
Body Length:
0.679 inches
Body Width:
0.679 inches
Body Height:
2.950 inches
Case Material:
Metal
Actuator Length:
Between 1.160 inches and 1.180 inches
Actuator Style:
Rectangular
Actuator Height:
Between 0.260 inches and 0.280 inches
Actuator Width:
Between 0.910 inches and 0.930 inches
Actuator Color:
Black single actuator
Illuminated Actuator Color:
Red single actuator
Actuator Inscription:
Request data single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
2 two circuit, double break/double make, one position momentary single switch unit

NSN 5930-01-272-4146

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0