## NSN 5930-01-272-4146

**Hazardous Locations/environmental Protection:** 

Push Switch - Page 1 of 2

Humidity resistant and explosion proof

Between 1.240 inches and 1.260 inches

**Body Style:** Panel mount

**Overall Length:** 

Overall Height: 3.430 inches



View Online at https://aerobasegroup.com/nsn/5930-01-272-4146

Overall Width:
Between 0.990 inches and 1.010 inches
Body Length:
0.679 inches
Body Width:
0.679 inches
Body Height:
2.950 inches
Case Material:
Metal
Actuator Length:
Between 1.160 inches and 1.180 inches
Actuator Style:
Rectangular
Actuator Height:
Between 0.260 inches and 0.280 inches
Actuator Width:
Between 0.910 inches and 0.930 inches
Actuator Color:
Black single actuator
Illuminated Actuator Color:
Red single actuator
Actuator Inscription:
Request data single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
2 two circuit, double break/double make, one position momentary single switch unit

## NSN 5930-01-272-4146

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

**Precious Material And Location:** 

Contacts silver

**Terminal Type And Quantity:** 

1 socket, integrated wire termination

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0