

View Online at <https://aerobasegroup.com/nsn/5930-01-272-4149>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Humidity resistant and explosion proof

**Overall Length:**

Between 1.240 inches and 1.260 inches

**Overall Height:**

3.430 inches

**Overall Width:**

Between 0.990 inches and 1.010 inches

**Body Length:**

0.679 inches

**Body Width:**

0.679 inches

**Body Height:**

2.950 inches

**Case Material:**

Metal

**Actuator Length:**

Between 1.160 inches and 1.180 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

Between 0.260 inches and 0.280 inches

**Actuator Width:**

Between 0.910 inches and 0.930 inches

**Actuator Color:**

Black single actuator

**Illuminated Actuator Color:**

Red single actuator

**Actuator Inscription:**

Page forward single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

2 two circuit, double break/double make, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

**Precious Material And Location:**

Contacts silver

**Terminal Type And Quantity:**

1 socket, integrated wire termination

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0