NSN 5930-01-272-4153

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Explosion proof and humidity resistant

Body Style:Panel mounted

Overall Length: 3.430 inches Overall Height: 1.240 inches



View Online at https://aerobasegroup.com/nsn/5930-01-272-4153

Overall Width:					
Between 0.990 inches and 1.010 inches					
Body Width:					
0.750 inches					
Body Height:					
0.750 inches					
Case Material:					
Metal					
Actuator Length:					
Between 1.160 inches and 1.180 inches					
Actuator Style:					
Rectangular					
Actuator Height:					
Between 0.260 inches and 0.280 inches					
Actuator Width:					
Between 0.910 inches and 0.930 inches					
Actuator Color:					
Black single actuator					
Illuminated Actuator Color:					
Red single actuator and yellow single actuator					
Actuator Inscription:					
Range 1 mile single actuator					
Maximum Voltage Rating In Volts:					
115.0 ac and 28.0 dc					
Mounting Surface To Terminal End Distance:					
2.950 inches					
Inclosure Type:					
Fully enclosed					
Mounting Method:					
Panel					
Features Provided:					
Actuator seal and full display lens					
Nonpile-up Contact Arrangement:					
2 two circuit, double break/double make, one position momentary single switch unit					

NSN 5930-01-272-4153

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 1.000 amperes lamp ac

D۳	acione	Matoria	I And	Location:
71	ecious	wateria	II Ana	Location.

Contacts silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0