

View Online at <https://aerobasegroup.com/nsn/5930-01-272-4154>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

Overall Length:

3.430 inches

Overall Height:

Between 1.240 inches and 1.260 inches

Overall Width:

Between 0.990 inches and 1.010 inches

Body Width:

0.750 inches

Body Height:

0.679 inches

Case Material:

Metal

Actuator Length:

Between 1.160 inches and 1.180 inches

Actuator Style:

Rectangular

Actuator Height:

Between 0.260 inches and 0.280 inches

Actuator Width:

Between 0.910 inches and 0.930 inches

Actuator Color:

Black single actuator

Illuminated Actuator Color:

Red single actuator and yellow single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

2.950 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Actuator seal and holding mechanism and full display lens

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0