## NSN 5930-01-272-4154

Push Switch - Page 1 of 2

inductive ac and 1.000 amperes lamp ac



View Online at https://aerobasegroup.com/nsn/5930-01-272-4154

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
3.430 inches
Overall Height:
Between 1.240 inches and 1.260 inches
Overall Width:
Between 0.990 inches and 1.010 inches
Body Width:
0.750 inches
Body Height:
0.679 inches
Case Material:
Metal
Actuator Length:
Between 1.160 inches and 1.180 inches
Actuator Style:
Rectangular
Actuator Height:
Between 0.260 inches and 0.280 inches
Actuator Width:
Between 0.910 inches and 0.930 inches
Actuator Color:
Black single actuator
Illuminated Actuator Color:
Red single actuator and yellow single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
2.950 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Actuator seal and holding mechanism and full display lens
Nonpile-up Contact Arrangement:
2 two circuit, double break/double make, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes

## NSN 5930-01-272-4154

Push Switch - Page 2 of 2



Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
1 socket, integrated wire termination
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0