NSN 5930-01-272-4155

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-272-4155

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
3.430 inches
Overall Height:
Between 1.240 inches and 1.260 inches
Overall Width:
Between 0.990 inches and 1.010 inches
Body Width:
0.679 inches
Body Height:
0.750 inches
Case Material:
Metal
Actuator Length:
Between 1.160 inches and 1.180 inches
Actuator Style:
Rectangular
Actuator Height:
Between 0.260 inches and 0.280 inches
Actuator Width:
Between 0.910 inches and 0.930 inches
Actuator Color:
Black single actuator
Illuminated Actuator Color:
Black single actuator
Actuator Inscription:
Hi temp alarm single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
2.950 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Full display lens
Nonpile-up Contact Arrangement:
2 two circuit double break/double make, one position momentary single sy

2 two circuit, double break/double make, one position momentary single switch unit

NSN 5930-01-272-4155

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes

inductive ac and 1.000 amperes lamp ac

Special Features:

Sunlight readable; characters illuminate yellow

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0