## NSN 5930-01-272-4157



rush Switch - rage 1 of 2	Group
View Online at https://aerobasegroup.com/nsn/5930-01-272-4157	
Body Style:	
Panel mounted	
Hazardous Locations/environmental Protection:	
Explosion proof and humidity resistant	
Overall Length:	
3.430 inches	
Overall Height:	
Between 1.240 inches and 1.260 inches	
Overall Width:	
Between 0.990 inches and 1.010 inches	
Body Width:	
0.679 inches	
Body Height:	
0.750 inches	
Case Material:	
Metal	
Actuator Length:	
Between 1.160 inches and 1.180 inches	
Actuator Style:	
Rectangular	
Actuator Height:	
Between 0.260 inches and 0.280 inches	
Actuator Width:	
Between 0.910 inches and 0.930 inches	
Actuator Color:	
Black single actuator	
Illuminated Actuator Color:	
Red single actuator and yellow single actuator	
Actuator Inscription:	
Range 2 miles single actuator	
Maximum Voltage Rating In Volts:	
115.0 ac and 28.0 dc	
Mounting Surface To Terminal End Distance:	

2.950 inches

Inclosure Type:

Fully enclosed

**Mounting Method:** 

Panel

**Features Provided:** 

Actuator seal and full display lens

**Nonpile-up Contact Arrangement:** 

2 two circuit, double break/double make, one position momentary single switch unit

## NSN 5930-01-272-4157

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

Precious	Material	And I	Location:

Contacts silver

## **Terminal Type And Quantity:**

1 socket, integrated wire termination

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0