

View Online at <https://aerobasegroup.com/nsn/5930-01-272-5510>

**Thread Class:**

2a single threaded stud

**Overall Height:**

0.862 inches

**Body Height:**

Between 0.375 inches and 0.460 inches

**Overall Diameter:**

0.640 inches

**Mounting Method:**

Threaded stud

**Thready Qty Per Inch (tpi):**

32 single threaded stud

**Contact Action Stimulus:**

Decrease

**Thread Size:**

0.138 inches single threaded stud

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

2.0 amperes resistive load first voltage

**Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:**

95.00 actuation point degrees fahrenheit and 80.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

28.0 dc at sea level first voltage

**Frequency In Hertz:**

60.0 second voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Disc

**Test Data Document:**

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc single threaded stud

**Specification Data:**

81349-mil-s-24236/24 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0

**Mil-std (military Standard):**

Mil-s-24236 spec.