

View Online at <https://aerobasegroup.com/nsn/5930-01-272-5510>

Thread Class:

2a single threaded stud

Overall Height:

0.862 inches

Body Height:

Between 0.375 inches and 0.460 inches

Overall Diameter:

0.640 inches

Mounting Method:

Threaded stud

Thready Qty Per Inch (tpi):

32 single threaded stud

Contact Action Stimulus:

Decrease

Thread Size:

0.138 inches single threaded stud

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

2.0 amperes resistive load first voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

95.00 actuation point degrees fahrenheit and 80.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level first voltage

Frequency In Hertz:

60.0 second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Disc

Test Data Document:

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single threaded stud

Specification Data:

81349-mil-s-24236/24 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0

Mil-std (military Standard):

Mil-s-24236 spec.