NSN 5930-01-272-6171

Push Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-01-272-6171

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

Overall Length:

3.380 inches

Overall Height:

1.000 inches

Overall Width:

0.750 inches

Body Width:

0.750 inches

Body Height:

0.750 inches

Case Material:

Metal

Actuator Length:

1.000 inches

Actuator Style:

Rectangular

Actuator Height:

0.430 inches

Actuator Width:

0.750 inches

Illuminated Actuator Color:

Yellow single actuator

Actuator Inscription:

System failure single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

2.950 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Rfi shielding and full display lens

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac



NSN 5930-01-272-6171

Push Switch - Page 2 of 2



Precious Material And Location:

Contact silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0