

View Online at <https://aerobasegroup.com/nsn/5930-01-272-6261>

Body Style:

Bushing mount

Overall Length:

0.465 inches

Overall Height:

1.745 inches

Overall Width:

0.510 inches

Bushing Length:

0.390 inches

Body Length:

0.465 inches

Body Width:

0.510 inches

Body Height:

0.440 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

0.218 inches

Actuator Height:

0.660 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position momentary

Actuator Position-locking Relationship:

Down position locked in

Maximum Voltage Rating In Volts:

125.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

0.695 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac and 1.000 amperes lamp ac

Precious Material And Location:

Terminal surfaces gold or terminals silver

Test Data Document:

81349-mil-s-83731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 printed circuit

Specification Data:

81349-mils-83731/12 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0