

View Online at <https://aerobasegroup.com/nsn/5930-01-272-6261>

**Body Style:**

Bushing mount

**Overall Length:**

0.465 inches

**Overall Height:**

1.745 inches

**Overall Width:**

0.510 inches

**Bushing Length:**

0.390 inches

**Body Length:**

0.465 inches

**Body Width:**

0.510 inches

**Body Height:**

0.440 inches

**Case Material:**

Metal

**Actuator Style:**

Round

**Actuator Diameter:**

0.218 inches

**Actuator Height:**

0.660 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position momentary

**Actuator Position-locking Relationship:**

Down position locked in

**Maximum Voltage Rating In Volts:**

125.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

0.695 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, three positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac and 1.000 amperes lamp ac

**Precious Material And Location:**

Terminal surfaces gold or terminals silver

**Test Data Document:**

81349-mil-s-83731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 printed circuit

**Specification Data:**

81349-mils-83731/12 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0