NSN 5930-01-272-7117

Push Switch - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5930-01-272-7117 | |
|---|--|
| Body Style: | |
| Panel mounted | |
| Hazardous Locations/environmental Protection: | |
| Explosion proof and humidity resistant | |
| Overall Length: | |
| 3.380 inches | |
| Overall Height: | |
| 1.000 inches | |
| Overall Width: | |
| 0.750 inches | |
| Body Width: | |
| 0.750 inches | |
| Body Height: | |
| 1.000 inches | |
| Case Material: | |
| Metal | |
| Actuator Length: | |
| 1.000 inches | |
| Actuator Style: | |
| Rectangular | |
| Actuator Height: | |
| 0.430 inches | |
| Actuator Width: | |
| 0.750 inches | |
| Illuminated Actuator Color: | |
| Yellow single actuator and red single actuator | |
| Actuator Inscription: | |
| Collision avoidance single actuator | |
| Maximum Voltage Rating In Volts: | |
| 115.0 ac and 28.0 dc | |
| Mounting Surface To Terminal End Distance: | |
| 2.950 inches | |
| Inclosure Type: | |
| Fully enclosed | |
| Mounting Method: | |
| Panel | |
| Features Provided: | |
| Rfi shielding and full display lens | |
| Nonpile-up Contact Arrangement: | |
| 2 pole, double throw, one position momentary single switch unit | |
| Contact Load Current Pating At Maximum Pated Voltage: | |

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

NSN 5930-01-272-7117

Push Switch - Page 2 of 2



| Precious Material And Location: |
|---------------------------------------|
| Contact silver |
| Terminal Type And Quantity: |
| 1 socket, integrated wire termination |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A053a0