

View Online at <https://aerobasegroup.com/nsn/5930-01-272-7156>

**Thread Class:**

2a 2nd mounting facility

**Thread Length:**

0.250 inches 2nd mounting facility

**Hazardous Locations/environmental Protection:**

Shock resistant

**Overall Length:**

1.292 inches

**First Flat Length:**

0.250 inches single actuator

**Flat Height:**

0.094 inches single actuator

**Shaft Diameter:**

0.125 inches single actuator

**Shaft Length:**

0.375 inches single actuator

**Overall Diameter:**

0.500 inches

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Flatted bushing at 3: 00 o'clock flatted bushing at 9: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section rear

**Throw Quantity:**

4 single section rear

**Mounting Method:**

Printed circuit 1st mounting facility threaded bushing 2nd mounting facility

**Thread Size:**

0.250 inches 2nd mounting facility

**Contact Voltage Rating In Volts:**

115.0 ac at sea level 28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Printed circuit

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

36.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

150.0 milliamperes resistive load ac at sea level 200.0 milliamperes resistive load dc at sea level

**Precious Material And Location:**

Contact and terminal surfaces gold

**Precious Material:**

Gold

**Style Designator:**

Snap or line

**Thread Series Designator:**

Unf 2nd mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A052b0