## NSN 5930-01-272-7212

Push Switch - Page 1 of 2

Actuator seal



View Online at https://aerobasegroup.com/nsn/5930-01-272-7212

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Fungus resistant and humidity resistant and salt spray resistant and shock resistant and vibration resistant and watertight
Overall Length:
1.080 inches
Overall Height:
3.430 inches
Overall Width:
1.080 inches
Body Length:
1.080 inches
Body Width:
1.080 inches
Body Height:
3.160 inches
Case Material:
Metal
Actuator Length:
0.720 inches
Actuator Style:
Rectangular
Actuator Height:
0.270 inches
Actuator Width:
0.720 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
White single actuator
Actuator Inscription:
Emer off single actuator
Maximum Voltage Rating In Volts:
28.0 dc
End Application:
Osprey class mhc, avenger class mcm, mine countermeasures support (mcs) class (lph-12), anti-sub systems.
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:

## NSN 5930-01-272-7212

Push Switch - Page 2 of 2



Nonpile-up	Contact	<b>Arrangement:</b>
opo up	00111401	, agoo

4 pole, double throw, both positions maintained single switch unit

**Criticality Code Justification:** 

Feat

**Contact Load Current Rating At Maximum Rated Voltage:** 

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc

**Special Features:** 

Weapon system essential

**Precious Material And Location:** 

Contacts silver

**Terminal Type And Quantity:** 

16 turret

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0