NSN 5930-01-272-7212

Push Switch - Page 1 of 2

Actuator seal



View Online at https://aerobasegroup.com/nsn/5930-01-272-7212

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Fungus resistant and humidity resistant and salt spray resistant and shock resistant and vibration resistant and watertight
Overall Length:
1.080 inches
Overall Height:
3.430 inches
Overall Width:
1.080 inches
Body Length:
1.080 inches
Body Width:
1.080 inches
Body Height:
3.160 inches
Case Material:
Metal
Actuator Length:
0.720 inches
Actuator Style:
Rectangular
Actuator Height:
0.270 inches
Actuator Width:
0.720 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
White single actuator
Actuator Inscription:
Emer off single actuator
Maximum Voltage Rating In Volts:
28.0 dc
End Application:
Osprey class mhc, avenger class mcm, mine countermeasures support (mcs) class (lph-12), anti-sub systems.
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:

NSN 5930-01-272-7212

Push Switch - Page 2 of 2



Nonpile-up	Contact	Arrangement:
opo up	00111401	, u go o

4 pole, double throw, both positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc

Special Features:

Weapon system essential

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

16 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0