NSN 5930-01-272-8213

Push Switch - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5930-01-272-8213

Panel mounted					
Hazardous Locations/environmental Protection:					
Explosion proof and humidity resistant					
Overall Length:					
4.040 inches					
Overall Height:					
0.990 inches					
Overall Width:					
0.990 inches					
Body Width:					
0.990 inches					
Body Height:					
0.990 inches					
Case Material:					
Metal					
Actuator Length:					
0.740 inches					
Actuator Style:					
Rectangular					
Actuator Height:					
0.270 inches					
Actuator Width:					
0.740 inches					
Actuator Color:					
White single actuator and green single actuator					
Illuminated Actuator Color:					
White single actuator and green single actuator					
Actuator Inscription:					
Wcc2/enable single actuator					
Maximum Voltage Rating In Volts:					
30.0 dc					
Mounting Surface To Terminal End Distance:					
3.770 inches					
Inclosure Type:					
Fully enclosed					
Mounting Method:					
Panel					
Features Provided:					
Actuator seal and rfi shielding and holding solenoid and horizontal split lens					
Nonpile-up Contact Arrangement:					
4 pole, double throw, both positions maintained single switch unit					

NSN 5930-01-272-8213

Push Switch - Page 2 of 2



Contact Load	l Current	Rating	At Maximum	Rated	Voltage:
Juliaul Luai	a Guileii	ivatiliy	AL WIGAIIIIUIII	Nateu	V Oitage.

250.000 milliamperes resistive dc

Special Features:

Actuator is horozontally split

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0