## NSN 5930-01-273-2087

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-273-2087

View Online at https://aerobasegroup.com/nsn/5930-01-273-2087
Overall Length:
1.220 inches
Overall Height:
0.400 inches
Body Diameter:
0.610 inches
Body Height:
0.310 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Distance Between Mounting Facility Centers:
0.937 inches
Tempurature Sensing Element Type:
Internal sensor
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Two position in-line Nonpile-up Contact Arrangement:
Nonpile-up Contact Arrangement:
Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action
Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action Terminal Type:
Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action Terminal Type: Tab, solder lug
Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating:
Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 6.5 amperes resistive load third voltage
Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 6.5 amperes resistive load third voltage Contact Adjustability:
<ul> <li>Nonpile-up Contact Arrangement:</li> <li>1 pole, single throw, normally open, momentary action</li> <li>Terminal Type:</li> <li>Tab, solder lug</li> <li>Contact Load Current Rating:</li> <li>6.5 amperes resistive load third voltage</li> <li>Contact Adjustability:</li> <li>Actuation point not adjustable and deactuation point not adjustable</li> </ul>
<ul> <li>Nonpile-up Contact Arrangement:</li> <li>1 pole, single throw, normally open, momentary action</li> <li>Terminal Type:</li> <li>Tab, solder lug</li> <li>Contact Load Current Rating:</li> <li>6.5 amperes resistive load third voltage</li> <li>Contact Adjustability:</li> <li>Actuation point not adjustable and deactuation point not adjustable</li> <li>Contact Stimulus Rating:</li> </ul>
<ul> <li>Nonpile-up Contact Arrangement:</li> <li>1 pole, single throw, normally open, momentary action</li> <li>Terminal Type:</li> <li>Tab, solder lug</li> <li>Contact Load Current Rating:</li> <li>6.5 amperes resistive load third voltage</li> <li>Contact Adjustability:</li> <li>Actuation point not adjustable and deactuation point not adjustable</li> <li>Contact Stimulus Rating:</li> <li>60.00 actuation point degrees fahrenheit and 40.00 deactuation point degrees fahrenheit</li> </ul>
<ul> <li>Nonpile-up Contact Arrangement:</li> <li>1 pole, single throw, normally open, momentary action</li> <li>Terminal Type:</li> <li>Tab, solder lug</li> <li>Contact Load Current Rating:</li> <li>6.5 amperes resistive load third voltage</li> <li>Contact Adjustability:</li> <li>Actuation point not adjustable and deactuation point not adjustable</li> <li>Contact Stimulus Rating:</li> <li>60.00 actuation point degrees fahrenheit and 40.00 deactuation point degrees fahrenheit</li> <li>Contact Voltage Rating In Volts:</li> </ul>
Nonpile-up Contact Arrangement: <ol> <li>pole, single throw, normally open, momentary action</li> </ol> Terminal Type: Tab, solder lug Contact Load Current Rating: 6.5 amperes resistive load third voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating: 60.00 actuation point degrees fahrenheit and 40.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level third voltage
Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action <b>Terminal Type:</b> Tab, solder lug Contact Load Current Rating: 6.5 amperes resistive load third voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating: 60.00 actuation point degrees fahrenheit and 40.00 deactuation point degrees fahrenheit Sold cat sea level third voltage Frequency In Hertz:
Nonpile-up Contact Arrangement:1 pole, single throw, normally open, momentary actionTerminal Type:Tab, solder lugContact Load Current Rating:6.5 amperes resistive load third voltageContact Adjustability:Actuation point not adjustable and deactuation point not adjustableContact Stimulus Rating:60.00 actuation point degrees fahrenheit and 40.00 deactuation point degrees fahrenheit30.0 dc at sea level third voltageFrequency In Hertz:60.0 second voltage
Nonpile-up Contact Arrangement: <ol> <li>pole, single throw, normally open, momentary action</li> </ol> Terminal Type: Tab, solder lug Contact Load Current Rating: 6.5 amperes resistive load third voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating: 60.00 actuation point degrees fahrenheit and 40.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level third voltage Frequency In Hertz: 60.0 second voltage Media For Which Designed:
Nonpile-up Contact Arrangement: <ol> <li>pole, single throw, normally open, momentary action</li> </ol> Terminal Type: Tab, solder lug Contact Load Current Rating: 6.5 amperes resistive load third voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating: 60.00 actuation point degrees fahrenheit and 40.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level third voltage Frequency In Hertz: 60.0 second voltage Media For Which Designed: Gas
Nonpile-up Contact Arrangement:1 pole, single throw, normally open, momentary actionTerminal Type:Tab, solder lugContact Load Current Rating:6.5 amperes resistive load third voltageContact Adjustability:Actuation point not adjustable and deactuation point not adjustableContact Stimulus Rating:60.00 actuation point degrees fahrenheit and 40.00 deactuation point degrees fahrenheit30.0 dc at sea level third voltageFrequency In Hertz:60.0 second voltageMedia For Which Designed:GasStyle Designator:

N/a

## NSN 5930-01-273-2087

Thermostatic Switch - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A048b0

