

View Online at <https://aerobasegroup.com/nsn/5930-01-273-2092>

**Thread Class:**

2b single mounting facility

**Hazardous Locations/environmental Protection:**

Shock proof

**Overall Length:**

5.687 inches

**Overall Height:**

2.875 inches

**Overall Width:**

2.500 inches

**Individual Section Quantity:**

6

**Longest Horizontal Distance Between Mounting Centers:**

1.062 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

1.062 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

**Features Provided:**

Actuator knob and legend plate

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.164 inches single mounting facility

**Contact Voltage Rating In Volts:**

440.0 highest ac voltage rating at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Terminal Type:**

Tab w/screw

**Switch Actuator Positioning Increment:**

36.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

4.0 amperes inductive load lowest ac voltage rating at sea level

**Special Features:**

Legend plate reads flow start, flow forward, stop reset

**Style Designator:**

In-line, cam actuated

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0