NSN 5930-01-273-2916

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-273-2916

Thread	Class:

2b all threaded hole

Overall Length:

1.656 inches

Overall Height:

3.188 inches

Overall Width:

2.390 inches

Body Height:

2.375 inches

Distance Between Mounting Facility Centers:

1.750 inches

Capillary Tube Length:

60.0 inches

Bulb Length:

5.500 inches

Bulb Diameter:

0.375 inches

Tempurature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Bracket and threaded hole

Thready Qty Per Inch (tpi):

32 all threaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.138 inches all threaded hole

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab w/screw

Contact Load Current Rating:

25.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+100.00/+200.00 actuation point degrees fahrenheit and +100.00/+200.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point shaft with scale and external deactuation point shaft with scale

NSN 5930-01-273-2916

Thermostatic Switch - Page 2 of 2



Contact Voltage Rating In Volts: 250.0 ac at sea level single voltage Media For Which Designed: Liquid Style Designator: Rectangular **Thread Series Designator:** Unc all threaded hole Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A048b0
