

View Online at <https://aerobasegroup.com/nsn/5930-01-273-3491>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Dustproof and driptight

Overall Length:

0.960 inches

Overall Height:

2.360 inches

Overall Width:

0.960 inches

Body Length:

0.689 inches

Body Width:

0.689 inches

Body Height:

1.820 inches

Case Material:

Metal

Actuator Length:

0.930 inches

Actuator Style:

Rectangular

Actuator Height:

0.275 inches

Actuator Width:

0.930 inches

Actuator Color:

Black single actuator

Illuminated Actuator Color:

Green single actuator and red single actuator and yellow single actuator

Actuator Inscription:

Booster armed, on, flt/ovrd single actuator

Illuminated Actuator Color Sequence:

Top half of actuator yellow lower left quarter of actuator green lower right quarter of actuator red

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

Special Features:

Emi shield, sunlight readable, three way split screen

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

5 tab, solder lug and 3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0