

View Online at <https://aerobasegroup.com/nsn/5930-01-273-4170>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Dustproof and driptight

**Overall Length:**

0.960 inches

**Overall Height:**

2.360 inches

**Overall Width:**

0.960 inches

**Body Length:**

0.688 inches

**Body Width:**

0.688 inches

**Body Height:**

1.820 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.450 inches

**Actuator Color:**

Black single actuator

**Illuminated Actuator Color:**

Yellow single actuator and green single actuator and red single actuator

**Actuator Inscription:**

Missile away, on, flt ovrd single actuator

**Illuminated Actuator Color Sequence:**

Upper half of actuator yellow, lower left half of actuator green, lower right half of actuator red

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 0.500 amperes inductive dc

**Special Features:**

Three-way split lens, emi shielded

**Precious Material And Location:**

Contacts gold

**Terminal Type And Quantity:**

5 tab, solder lug and 3 turret

**Specification Data:**

53711-5408724 manufacturers source control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0