## NSN 5930-01-273-5335

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-273-5335

Body Style: Panel mount  Hazardous Locations/environmental Protection:  Dustproof and driptight  Overall Length:  0.960 inches  Overall Height:  2.360 inches  Overall Width:  0.960 inches
Hazardous Locations/environmental Protection:  Dustproof and driptight  Overall Length:  0.960 inches  Overall Height:  2.360 inches  Overall Width:  0.960 inches
Dustproof and driptight  Overall Length:  0.960 inches  Overall Height:  2.360 inches  Overall Width:  0.960 inches
Overall Length:  0.960 inches  Overall Height:  2.360 inches  Overall Width:  0.960 inches
0.960 inches  Overall Height: 2.360 inches  Overall Width: 0.960 inches
Overall Height: 2.360 inches Overall Width: 0.960 inches
2.360 inches  Overall Width:  0.960 inches
Overall Width: 0.960 inches
0.960 inches
Body Length:
0.689 inches
Body Width:
0.689 inches
Body Height:
1.820 inches
Case Material:
Metal
Actuator Length:
0.930 inches
Actuator Style:
Rectangular
Actuator Height:
0.275 inches
Actuator Width:
0.930 inches
Actuator Color:
Black single actuator
Illuminated Actuator Color:
Green single actuator and red single actuator and yellow single actuator
Actuator Inscription:
Warhead safed, on, flt/ovrd single actuator
Illuminated Actuator Color Sequence:
Top half of actuator yellow lower left quarter of actuator green lower right quarter of actuator red
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

## NSN 5930-01-273-5335

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

**Special Features:** 

Emi shield, sunlight readable, three way split lens

**Precious Material And Location:** 

Contacts gold

**Terminal Type And Quantity:** 

5 tab, solder lug and 3 turret

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0