NSN 5930-01-273-6335

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-273-6335

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Industrial use
Overall Length:
1.974 inches
Overall Height:
1.825 inches
Overall Width:
0.550 inches
Body Length:
1.520 inches
Body Width:
0.550 inches
Body Height:
1.825 inches
Case Material:
Metal or plastic
Unthreaded Mounting Hole Diameter:
0.138 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.510 inches
Actuator Style:
Round
Actuator Diameter:
0.255 inches
Actuator Height:
0.375 inches
Actuator Free Position Height:
0.375 inches
Maximum Voltage Rating In Volts:
250.0 ac and 250.0 dc
Inclosure Type:
Uninclosed
Mounting Method:
Threaded hole and unthreaded hole
Thready Qty Per Inch (tpi):
32
Thread Size:
0.138 inches
Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

NSN 5930-01-273-6335

Sensitive Switch - Page 2 of 2



Δ	ctu	ato	- М	ΛV/	am.	۵ni	ŀ
н	CLU	alu	IVI	OVE	2111		L.

0.172 pretravel inches and 0.078 overtravel inches and 0.078 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

0.250 amperes resistive dc and 15.000 amperes resistive ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

3 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0