Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-273-7971

Hazaro	dous Locations/environmental Protection:
Shock	proof and watertight
Overal	I Length:
3.520 i	nches
Overal	ll Height:
1.740 i	-
Overal	ll Width:
2.120 i	nches
Unthre	eaded Mounting Hole Diameter:
	nches single mounting facility
	lual Section Quantity:
1	
Longe	st Horizontal Distance Between Mounting Centers:
1.620 i	nches single mounting facility
Longe	st Vertical Distance Between Mounting Centers:
-	nches single mounting facility
Switch	n Contact Basic Design:
Nonpile	e-up nonsymmetrical
Mount	ing Method:
Bracke	t single mounting facility and unthreaded hole single mounting facility
Featur	es Provided:
Actuate	or knob and legend plate
Conta	ct Voltage Rating In Volts:
440.0 a	ac at sea level
Mount	ing Facility Pattern:
Four p	osition rectangular single mounting facility
Switch	Actuator Indexing Position Quantity:
3 singl	e actuator
Termir	nal Type:
Tab w/	screw
Conta	ct Load Current Rating:
10.0 ar	nperes inductive load dc at sea level
Specia	al Features:
Legend	d plate reads off and close water
Style [	Designator:
Tap, s	quare frame
Shelf I	_ife:
N/a	
Unit O	f Measure:
Demili	tarization:
No	

## NSN 5930-01-273-7971

Rotary Switch - Page 2 of 2

Fiig: A052b0

