

View Online at <https://aerobasegroup.com/nsn/5930-01-273-7974>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof and moisture resistant

Overall Length:

1.270 inches

Overall Height:

2.520 inches

Overall Width:

0.635 inches

Bushing Length:

0.470 inches

Body Length:

1.270 inches

Body Width:

0.635 inches

Body Height:

0.930 inches

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

0.690 inches

Actuator Position-action Relationship:

Up position momentary and center position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 10.000 amperes inductive dc and 4.000 amperes lamp dc and 15.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Test Data Document:

81349-mil-s-3950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 turret

Specification Data:

96906-ms27734 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0